

150 Motor Parkway | Suite 410 | Hauppauge, NY 11788 • TEL: 800-283-3888
email: weanchor@h-b.com | www.diedrichtechnologies.com

505 SPECIAL COATINGS STRIPPER

1. PRODUCT DATA

Product Name: 505 Special Coatings Stripper
Producer: Diedrich Technologies,
A Hohmann & Barnard Company,
150 Motor Parkway, Suite 410, Hauppague, NY 11788
Company Contact: Jonathon Byrge
Telephone: 800-283-3888
24-Hour Emergency Contact: CHEMTREC 800-424-9300

This product is manufactured for Commercial/Industrial use. Not recommended for: Household use.

2. HAZARDS IDENTIFICATION

GHS Ratings:

Skin irritation: 2

Eye irritation: 2A

Carcinogenicity: 2

Inhalation: 2

Single target organ toxicity – single exposure: 3

GHS Hazards

H315 Causes Skin irritation, burns

H319 Causes serious eye irritation, burns

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H351 Suspected of causing cancer

H373 May cause damage to organs (central nervous system) through prolonged or repeated exposure if inhaled

GHS Precautions

P201 Obtain specific instructions before use.

P202 Do not use until safety precautions have been read and understood.

P260 Do not breathe fumes.

P264 Wash skin thoroughly after handling.

P271 Use out of doors or in well ventilated areas.

P280 Wear protective gloves/eye protection/face protection.

P362 Take off contaminated clothing and wash before reuse.

P302+P352

IF ON SKIN: Wash off with plenty of soap and water.

P304+P340

IF INHALED: Get to fresh air

P305+P351+P338

IF IN EYES: Wash with water for several minutes

– get medical attention.

P403+P233

Store in a well ventilated area out of direct sunlight. Keep container closed

P501 Dispose of contents/container at an approved facility.

Warning



Hazards Not Otherwise Classified: None

3. COMPOSITION

Chemical Name/CAS No.	% Weight	OSHA PEL	OSHA TWA
75-09-2 Dichloromethane	70-80	25 ppm	25 ppm
67-56-1 Methanol	5-15	200 ppm	200 ppm
111-76-2 2-Butoxyethanol	1-10	50 ppm	50 ppm
141-43-5 Ethanolamine	1-5	6 ppm	3 ppm

4. FIRST AID MEASURES

Eyes: Flush with large amounts of water, lifting upper and lower lids. Get medical attention.

Ingestion: Call Physician, poison control center, or hospital emergency room. Never give anything by Mouth to an unconscious person.

Skin: Thoroughly wash exposed area with soap & water. Remove contaminated clothing Wash contaminated clothing before reuse.

Inhalation: If affected, remove individual to fresh air. If breathing is difficult, administer respiration. Keep person warm, quiet, and get medical attention.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Water spray, alcohol-resistant foam, dry chemical, or carbon dioxide

Unsuitable Extinguishing Media: no data available

Fire Fighting Instructions: Self-contained breathing apparatus with a full face piece operated in pressure demand or other positive pressure mode.

150 Motor Parkway | Suite 410 | Hauppauge, NY 11788 • TEL: 800-283-3888
email: weanchor@h-b.com | www.diedrichtechnologies.com

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures: Use personal protective equipment. Avoid breathing vapors. Ensure Adequate ventilation. Evacuate personnel to safe areas.

Environmental Precautions: Prevent further leakage or spillage if safe to do so.

Methods for Containment: Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable closed containers for disposal.

7. HANDLING AND STORAGE

Handling Precautions: Avoid contact with skin and eyes. Avoid inhalation of vapors or mists.

Storage: Store in a cool, dry, well ventilated space out of direct sunlight.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Engineering controls: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Ensure that eyewash stations and safety showers are close to the workstation location.

Ventilation Control: Controlling airborne concentrations below the ACGIH TLV exposure guideline is recommended. ADGIH TWA is 50ppm. OSHA PEL is 25 ppm 8 hour TWA, and a STEL is 125 ppm. This rule also establishes an Action Level of 12.5 ppm. Use only with adequate ventilation. Local exhaust ventilation is necessary for most applications. Lethal concentrations may exist in areas with poor ventilation. Medical monitoring is also required by OSHA for applications that exceed the Action Level of 12.5ppm.

Administrative controls: No data found.

Protective Clothing: Splash goggles / Face Shield, Chemical resistant gloves, Chemical resistant apron and proper foot protections.

Eye Protection: Use safety glasses. Where contact is likely, use chemical splash goggles.

Hand Protection: Wear appropriate safety gloves

Skin & Body Protection: Avoid contact with skin and avoid breathing vapors. Do not eat, drink, or smoke in work area. Wash hands prior to eating, drinking, or using restroom. Any clothing or shoes that have been contaminated should be removed immediately and thoroughly and laundered before wearing again.

Respiratory Protection: Atmospheric levels should be maintained below the exposure guideline. If this level is exceeded, use an approved air supplied respirator. For emergency and other conditions where the exposure guideline may be greatly exceeded, use an approved positive pressure self-contained breathing apparatus.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Appearance: Light in color

Odor: Typical Methylene chloride odor

pH: 10-12

Boiling Point: 104 (Initial)

Density: 10 lbs./gal.

Vapor Density: 2.93 (Air = 1)

Specific Gravity: 1.190

Percent Volatile: >95.0%

VOC Emission Content: 154.7 grams/liter

Flash Point: None to boiling point

Auto-ignition Temperature: Not Determined

Flammable Limits (UEL & LEL): No data found

Weight Per Gallon: 11.2 lbs

10. STABILITY AND REACTIVITY

Reactivity: No data available

Stability: Stable under recommended storage conditions

Possibility of Hazardous Reactions: No data available

Conditions to Avoid: Heat, flame, and sparks. Exposure to sunlight.

Incompatible Materials: Alkali metals, aluminum, strong oxidizing agents, strong acids.

Hazardous Decomposition Products: Open flames and welding arcs can cause thermal decomposition with the evolution of hydrogen chloride and very small amounts of phosgene and chlorine.

11. TOXICOLOGICAL INFORMATION

Information on Toxicological Affects:

LD50 Oral – Rat >2,000 mg/kg

Respiratory or Skin Sensitization:

LC50 inhalation – rat 52,000mg/m³;

Skin irritation and eye irritation on contact

Carcinogenetic: Limited evidence of carcinogenicity in animal studies

IARC 2B: Possible carcinogenic to humans.

OSHA: OSHA specifically regulated carcinogen (dichloromethane)

150 Motor Parkway | Suite 410 | Hauppauge, NY 11788 • TEL: 800-283-3888
email: weanchor@h-b.com | www.diedrichtechnologies.com

Reproductive Toxicity: no data available

Symptoms/Injuries after Inhalation: Dichloromethane is metabolized in the body producing carbon monoxide which increased and sustains carboxyhemoglobin levels in the blood, reducing oxygen-carrying capacity of the blood. Acts as a simple asphyxiant by displacing air – anesthetic affects. Difficulty in breathing, headaches, dizziness.

Symptoms/Injuries after Eye Contact: Redness, blurred vision, tears, burns on extended contact.

Symptoms/Injuries after Ingestion: Gastrointestinal irritation, central nervous system depression, abdominal pain.

12. ECOLOGICAL INFORMATION

Keep out of waterways.

13. DISPOSAL

Dispose of in accordance with local, regional, national and international regulations.

14. TRANSPORTATION INFORMATION

The following is for US DOT Highway transportation. Other modes/jurisdictions may have different classifications.

Agency	Proper Shipping Name	UN Number	Packaging Group	Hazard Class
US DOT	Corrosive Paint Related Material	UN3066	II	8

15. REGULATORY INFORMATION

Materials Listed on the United States TSCA (Toxic Substance Control Act) Inventory

16. OTHER INFORMATION


Date of Preparation: July 1st, 2016

Revision Date: June 16th, 2023

Hazardous Material Information System (HMIS)

Health	3
Flammability	1
Physical Hazard	0
Personal Protection	[H]

National Fire Protection Association (NFPA)



HMIS & NFPA Hazard Rating Legend

- * = CHRONIC HEALTH HAZARD
- 0 = INSIGNIFICANT
- 1 = SLIGHT
- 2 = MODERATE
- 3 = HIGH

LEGEND

0 = LEAST 1 = SLIGHT 2 = MODERATE 3 = HIGH 4 = EXTREME
N.D. = NOT DETERMINED N.A. = NOT AVAILABLE N/A = NOT APPLICABLE

DISCLAIMER: While this company believes that the data contained herein are factual and the opinions expressed are based on tests and data believed to be reliable, it is the user's responsibility to determine the safety, toxicity and suitability for his own use of the product described herein. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by this company as to the effects of such use, the results to be obtained, or the safety and toxicity of the product, nor does this company assume any liability arising out of use, by others, of the product referred to herein. Nor is this information herein to be construed as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or governmental regulations.

REQUIRED SUPPLEMENTAL CONTRACT TERMS: Failure to obtain a property owner's written acceptance of the enclosed Required Supplemental Terms and Conditions for Restoration Contract shall release any and all of the manufacturer's express or implied warranties (including, without limitation, merchantability and fitness for particular purpose) and user shall indemnify and hold manufacturer harmless from all liability cost and expenses arising in any way from use of or contact with this product. All claims of any kind against manufacturer arising from or related to this product in any way shall be decided by binding arbitration in accordance with the Construction Industry Arbitration Rules of the American Arbitration Association.

Copyright © 2016

Diedrich Technologies is a division of



Hohmann & Barnard, Inc.
150 Motor Parkway | Suite 410 | Hauppauge, NY 11788
TEL: 800-645-0616 | FAX: 631-234-0683
EMAIL: weanchor@h-b.com | www.h-b.com